

- P PS/2 INTERFACE (6 PIN MINI DIN CONNECTOR, 9.5 FT. DEFAULT LENGTH)
- U USB INTERFACE (9.5 FT. DEFAULT LENGTH)
- 1 RS232 REF: DRAWING 811610 CABLE OPTION, 6.0 FT. DEFAULT LENGTH
- 2 RS422/RS485 (CUSTOM PART No.)


USE ONLY IF POWER OPTION IS "0"

- Q RS232 OPTIONAL CABLE REF. 811610 (CUSTOM CABLE LEGACY ONLY)

- DZ LOW TEMPERATURE AND CONFORMAL COATED PCB (-40°C TO 80°C)
- Z CONFORMAL COATED PCB
- V VIBRATION DAMPENED

ORDERING INFORMATION:

- POWER OPTION
- 0 STANDARD
 - 1 OPTIONAL RS232 POWER ADAPTOR CABLE



- 2B 2 BUTTON PS/2 MOUSE (LEGACY)
- 3B OR BLANK 3 BUTTON PS/2 MOUSE (DEFAULT)
- MSOF MICROSOFT SERIAL MOUSE (RS232 LEGACY)

SPECIFICATIONS SUBJECT TO CHANGE WITHOUT NOTICE

CTI ELECTRONICS CORPORATION
WWW.CTIELECTRONICS.COM

NEMA 12 (IP54) PANEL MOUNT
INDUSTRIAL TRACKBALL 3.0" DIAMETER
T4003 SERIES

761266

SCALE 3/4

APPROVED

DATE 08-14-13

DRAWN BY
PSB