



P PS/2 INTERFACE (6 PIN MINI DIN CONNECTOR, 9.5 FT. DEFAULT CABLE LENGTH)
 U USB INTERFACE (9.5 FT. DEFAULT CABLE LENGTH)

[W1] THRU [W5] INDICATES OPTIONAL BULKHEAD CONNECTOR,
 1 THRU 5 FOOT CABLE LENGTH IN 1 FT. INCREMENTS. (MATING CABLE INCLUDED)
 [W] IS 6 FT. CABLE WITH OPTIONAL BULKHEAD CONNECTOR PS/2 ONLY (LEGACY).

3 OR 33 ONLY

ORDERING INFORMATION:

K I F 9 0 [] [] [] [] - N [] [] []

2B, 3B OR BLANK PS/2, 2B OR 3B MOUSE EMULATION (LEGACY)
 FR FRENCH ``AZERTY'' (GRAY ELASTOMER)
 ES SPANISH ``QWERTY'' (GRAY ELASTOMER)
 DL GERMAN ``QWERTZ'' (GRAY ELASTOMER)
 BLANK IS DEFAULT US ``QWERTY'' (GRAY/BLACK ELASTOMER)

G MAXIMUM COMPRESSION SPRING OPTION.
 RF CONDUCTIVE BOOT OPTION.

1 GRAY ELASTOMER WITH SYN-PROOF COATING (WAS No.9)
 4 BLACK ELASTOMER WITH SYN-PROOF COATING (WAS No.5)

SPECIFICATION:

TEMPERATURE: -40°C TO +80°C
 SEALING: NEMA 4 (IP66)
 WEIGHT: APPROX. 7lbs 5oz [3.32 KILOGRAMS] WITH N33 KNOB (OPTIONAL)
 APPROX. 7lbs 5.5.oz [3.33 KILOGRAMS]
 STANDARDS: CE, ROHS, REACH, FCC CLASS B

NOTE: DIMENSIONS ARE IN INCHES MILLIMETERS

CTI ELECTRONICS CORPORATION WWW.CTIELECTRONICS.COM		
NEMA 4X KEYBOARD KIF9000-N3 SERIES W/INDUSTRIAL MOUSE (116 KEYS)		
761692		DATE 01-05-17
APPROVED	SHEET 1 OF 1	DRAWN BY PSB
COPYRIGHT 2017 CTI ELECTRONICS CORP. SPECIFICATIONS SUBJECT TO CHANGE WITHOUT NOTICE		