



ORDERING INFORMATION:

- 1 GRAY ELASTOMER WITH SYN-PROOF COATING<sup>TM</sup>
- 4 BLACK ELASTOMER WITH SYN-PROOF COATING<sup>TM</sup>
- 5 BLACK ELASTOMER
- 9 GRAY ELASTOMER

- [W] INDICATES OPTIONAL PS/2 KEYBOARD WITH "W" TYPE BULKHEAD CONNECTOR
- [1] THRU [5] INDICATES "W" CABLE LENGTH DIMENSION IN 1 FOOT INCREMENTS
- BLANK INDICATES DEFAULT CABLE LENGTH OF 6 FEET

KNOB OPTION 2 24 3 33 5 54

OPTIONS (BLANK INDICATES DEFAULT)

- 5C SUN VERSION (LEGACY)
- 2B 2 BUTTON PS/2 MOUSE (LEGACY)
- 3B 3 BUTTON PS/2 MOUSE (DEFAULT)
- MSOF MICROSOFT SERIAL MOUSE
- ES SPANISH
- FR FRENCH
- DL GERMAN

- P PS/2 INTERFACE (6 PIN MINI DIN CONNECTOR, 9.5 FT. DEFAULT LENGTH)
- 1 "AT" KEYBOARD INTERFACE AND SERIAL MOUSE (5 PIN CIRCULAR DIN & D9F CONNECTOR, 6.0 FT. DEFAULT LENGTH)
- U USB INTERFACE (9.5 FT. DEFAULT LENGTH)
- S SUN KEYBOARD AND MOUSE (8 PIN MINI DIN CONNECTOR, 6.0 FT. DEFAULT LENGTH) (LEGACY)

- I STANDARD QWERTY (IBM)
- C SUN LEGEND

STAINLESS STEEL ENCLOSURE

<b>CTI</b> ELECTRONICS CORPORATION	
110 Old South Ave., Stratford, CT 06615 - Tel 203 / 386-9779 - Fax 203 / 378-4986 - www.ctieletronics.com	
TITLE: <b>NEMA 4X KEYBOARD KXF90XX-NX SERIES W / INDUSTRIAL MOUSE<sup>®</sup> (116 KEYS)</b>	
REV. <b>d</b>	DATE: 09-09-04
APPROVED:	DRAWN: VI / SJS
<b>B 761692</b>	