



ORDERING INFORMATION:

- 0 GRAY ELASTOMER
- 1 GRAY ELASTOMER WITH SYN-PROOF COATING<sup>TM</sup>
- 4 BLACK ELASTOMER WITH SYN-PROOF COATING<sup>TM</sup>
- 5 BLACK ELASTOMER

[W] INDICATES OPTIONAL "W" TYPE BULKHEAD CONNECTOR

[1] THRU 5 INDICATES "W" CABLE LENGTH DIMENSION IN 1 FOOT INCREMENTS  
BLANK [ ] INDICATES DEFAULT CABLE LENGTH OF 6 FEET

- I STANDARD QWERTY (IBM)
- C SUN LEGEND

STAINLESS STEEL ENCLOSURE

K 80

- 5C SUN VERSION (LEGACY)
- ES SPANISH
- FR FRENCH
- DL GERMAN

- P PS/2 INTERFACE (6 PIN MINI DIN CONNECTOR, 9.5 FT. DEFAULT LENGTH)
- T "AT" INTERFACE (5 PIN CIRCULAR DIN CONNECTOR, 6.0 FT. DEFAULT LENGTH)
- U USB INTERFACE (9.5 FT. DEFAULT LENGTH)
- S SUN INTERFACE (8 PIN MINI DIN CONNECTOR, 6.0 FT. DEFAULT LENGTH) (LEGACY)

<b>CTI</b> ELECTRONICS CORPORATION	
110 Old South Ave, Stratford, CT 06615 - Tel 203 / 386-9779 - Fax 203 / 378-4986 - www.ctielectronics.com	
TITLE: <b>KEYBOARD MODEL KX80XX SERIES</b>	
REV. DATE: 09-02-04	<b>B761693</b>
APPROVED: DRAWN: VI / SJS	