



1 GRAY ELASTOMER WITH SYN-PROOF COATING™ (WAS 0 OR 3)
 4 BLACK ELASTOMER WITH SYN-PROOF COATING™

Z CONFORMAL COATING ON CONTROLLER PCB (NOT ON MATRIX PCB)
 VZ STANDARD VIBRATION DAMPENING AND CONFORMAL COATING

2B/3B OR BLANK	PS/2,	2B OR 3B MOUSE EMULATION (LEGACY)
FR	FRENCH	``AZERTY'' (GRAY ELASTOMER)
ES	SPANISH	``QWERTY'' (BLACK ELASTOMER)
DL	GERMAN	``QWERTZ'' (BLACK ELASTOMER)
BLANK IS DEFAULT	US	``QWERTY'' (GRAY/BLACK ELASTOMER)

SPECIFICATION:

TEMPERATURE: -25°C TO +80°C

SEALING: ALL KEYS ARE NEMA 4 (IP66)
 TRACKBALL IS NEMA 12 (IP54)

SHOCK: 40G (N) 11 msec. per MIL-STD-810

WEIGHT: KEYBOARD WITH ALUMINUM ENCLOSURE APPROX. 32 OZ. (.90 KILOGRAMS)
 KEYBOARD WITH STAINLESS STEEL ENCLOSURE APPROX. 55 OZ. (1.6 KILOGRAMS)

STANDARDS: ☑ ROHS, REACH, FCC CLASS B

NOTE: DIMENSIONS ARE IN INCHES [MILLIMETERS]

ORDERING INFORMATION:

K I T 6

[W1] THRU [W5] INDICATES OPTIONAL BULKHEAD CONNECTOR, 1 THRU 5 FOOT CABLE LENGTH IN 1 FT. INCREMENTS. MATING CABLE INCLUDED

[W] IS 6 FT. DEFAULT, PS/2 ONLY (LEGACY)

P PS/2 KEYBOARD AND MOUSE
 U USB KEYBOARD AND MOUSE (CABLES ARE 9.5 FT. DEFAULT)

0 ALUMINUM ENCLOSURE, PAINTED BEIGE
 4 ALUMINUM ENCLOSURE, PAINTED BLACK
 6 STAINLESS STEEL ENCLOSURE

CTI ELECTRONICS CORPORATION WWW.CTIELECTRONICS.COM	
KIT6000 SERIES NEMA 12/IP54 INDUSTRIAL KEYBOARD WITH 1.3" DIA TRACKBALL	
761745	SHEET 1 OF 1
APPROVED	DATE 10-14-16 DRAWN BY PSB
COPYRIGHT 2016 CTI ELECTRONICS CORP. SPECIFICATIONS SUBJECT TO CHANGE WITHOUT NOTICE	