2.50
[63.50]

15.00 [381.00] SYM
FOR TWO MOUNTING HOLES ON BOTTOM PLATE

2.30 [58.42]

1.60 [40.64]

SEALED SILICONE KEYBOARD
WITH SYN-PROOF (TM) COATING

STAINLESS STEEL
ENCLOSURE

SILICONE GASKET

CTI ELECTRONICS

2.0 [50.80]
(X2)

#8-32 THREADED MOUNTING HOLES,
PROVIDED FOR SECURING KEYBOARD TO
WORKING SURFACE WITH TWO SCREWS,
HAVING A DEPTH OF THREAD BETWEEN
3/16" MIN. TO 3/8" MAX.

ORBITALMOUSE
POINTER

8.04
[204.22]

STAINLESS STEEL
BOTTOM PLATE

.13 [3.3]   THICK PAD (X6)
(MICROCELLULAR URETHANE)

20.00 [508.00]

ORDERING INFORMATION:

USB INTERFACE (9.5 FT. DEFAULT CABLE LENGTH)

GRAY ELASTOMER WITH SYN-PROOF™COATING   (WAS No.9)

W1 THRU W5 INDICATES OPTIONAL BULKHEAD CONNECTOR,
1 THRU 5 FOOT CABLE LENGTH IN 1 FT. INCREMENTS.(MATING CABLE INCLUDED)

K I 0 9 0 U I

" LEGACY PRODUCT ONLY"

CTI ELECTRONICS CORPORATION
WWW.CTIELECTRONICS.COM

NEMA 4X (IP66) INDUSTRIAL KEYBOARD
WITH ORBITALMOUSE®
(BUTTON STYLE POINTER)
K1090UI SERIES

761759

APPROVED | SHEET 1 OF 1

DATE 01-12-17
DRAWN BY   PSB