


ORDERING INFORMATION

PPS/2 INTERFACE (6 PIN MINI DIN CONNECTOR, 9.5 FT. DEFAULT LENGTH)  
 UUSB INTERFACE (9.5 FT. DEFAULT CABLE LENGTH)  
 1RS232 (REQUIRES EITHER A POWER CABLE ADAPTOR OR A "Q" CABLE OPTION,  
 6.0 FT. DEFAULT LENGTH)

Q RS232 OPTIONAL CABLE REF. B811610 (LEGACY)

ORDERING INFORMATION

0 STANDARD FOR #6-32 MOUNTING  
 1 OPTIONAL RS232 POWER ADAPTOR CABLE  
 3 OPTIONAL METRIC M3 MOUNTING  
 4 METRIC M4 MOUNTING (LEGACY)



FIRMWARE OPTIONS

— BLANK (DEFAULT) FOR PS/2 AND USB  
 MSOF = MICROSOFT 1 BUTTON SERIAL MOUSE (RS232/LEGACY)

— KNOB OPTION (REF DWG. B761252)

JOYSTICK OPTIONS

(BLANK INDICATES NO JOYSTICK OPTIONS)  
 D LOW TEMPERATURE RANGE (-40°C TO +80°C)  
 G MAXIMUM COMPRESSION SPRING  
 RF CONDUCTIVE BOOT AND FERRITE BEAD  
 T FLIGHT STICK PROGRAM USB ONLY (NON-MOUSE)  
 Z CONFORMAL COATING

NOTES :

- 1 CTI REFERENCE: H2XX3A, HOUSING USES ELASTOMER KEY PAD
- 2 A = 2.100 DIMENSION FOR ELASTOMER SILICONE SWITCH AS SHOWN
- 3 OPTIONAL: SPECIAL ORDER MECHANICAL SWITCH A = 2.150 DIMENSION
- 4 DEBURR SHARP EDGES

PANEL MOUNTING DETAIL

**CTI** ELECTRONICS CORPORATION  
 110 OLD SOUTH AVE, STRATFORD, CT 06615  
 WWW.CTIELECTRONICS.COM

NEMA 4X (IP66)  
 PANEL MOUNT INDUSTRIAL MOUSE™  
 H20X1-NX SERIES

**761812**

REV. A  
 SHEET 1 OF 1

APPROVED

DATE 10-22-10

DRAWN PSB