

WHITE SILICONE ELASTOMER,
BLUE LEGENDS, PARYLENE COATED

KEYPAD DETAIL

28 AWG RIBBON CABLE
8" TYPICAL

BROWN

YELLOW

FERRITE BEAD

MOUNTING DETAILS

R.075 [R1.91] (X4)


1.50 [38.10] (X2)

.76 [19.30]

1.00 [25.40]

1.98 [50.17]

CLEARANCE FOR #4 OR 3MM SCREW (X4)



ORDERING INFORMATION

F 6 U 6 [] - N24W - []

OPTIONAL CABLE LENGTH
DIMENSION IN 0.5 FOOT INCREMENTS
(MINIMUM LENGTH IS 1.0 FT,
MAXIMUM LENGTH IS 9.5 FT.)
BLANK [] INDICATES NO CABLE

G MAXIMUM COMPRESSION SPRING
Z CONFORMAL COATING

BLANK USB MOUSE EMULATION
T USB HID COMPLIANT FLIGHTSTICK EMULATION

USB INTERFACE

0 4-40 THREADED BRASS INSERTS
3 3MM THREADED BRASS INSERTS

NOTES

DIMENSIONS ARE IN INCHES [MILLIMETERS]

CTI ELECTRONICS CORPORATION

WWW.CTIELECTRONICS.COM

NEMA 4 (IP66) MEDICAL / CLEANROOM
OEM MEDICAL MOUSE OR USB FLIGHTSTICK
PARYLENE COATED, F60U6-N24W SERIES

761846

DATE 08-25-15

APPROVED

SHEET 1 OF 1

DRAWN BY PSB

COPYRIGHT 2015 CTI ELECTRONICS CORP.
SPECIFICATIONS SUBJECT TO CHANGE WITHOUT NOTICE