



ORDERING INFORMATION

M 2  U 6 T   - N 3 3 W

W1 THRU W5 INDICATES OPTIONAL BULKHEAD CONNECTOR,  
CABLE LENGTH IN 1 FT. INCREMENTS

Z CONFORMAL COATING OPTION

G STRONGEST SPRING OPTION

USB HID COMPLIANT GAME CONTROLLER

USB INTERFACE (9.5 FT. DEFAULT CABLE LENGTH)

0 STAINLESS STEEL ENCLOSURE

5 PAINTED ALUMINUM, ENCLOSURE BEIGE

PUSH BUTTON SWITCH (BLUE)  
WHITE BEZEL

WHITE PVC KNOB (N33W)  
WITH PARYLENE COATED

WHITE FDA SILICONE BOOT  
WITH PARYLENE COATING

3.10 [78.74]

20° MAX.  
DEFLECTION

REF.  
.96 [24.38]

1.53 [38.86]

.06 THICK.  
NEOPRENE GASKET

.13 THK.  
FOAM RUBBER  
FOOT (X4)

NOTES

DIMENSIONS ARE IN INCHES [MILLIMETERS]

**CTI** ELECTRONICS CORPORATION

WWW.CTIELECTRONICS.COM

M2XU6T-N33W SERIES NEMA 4X (IP66)  
HANDHELD MEDICAL FLIGHTSTICK,  
CLEANROOM MOTION CONTROLLER

**761852**

DRAWN BY PSB  
DATE 09-02-15

APPROVED

SHEET 1 OF 1

COPYRIGHT 2015 CTI ELECTRONICS CORP.  
SPECIFICATIONS SUBJECT TO CHANGE WITHOUT NOTICE