



P PS/2 INTERFACE (6 PIN MINI DIN CONNECTOR, 9.5 FT. DEFAULT CABLE LENGTH)  
 U USB INTERFACE (9.5 FT. DEFAULT CABLE LENGTH)

[W1] THRU [W5] INDICATES OPTIONAL BULKHEAD CONNECTOR,  
 1 THRU 5 FOOT CABLE LENGTH IN 1 FT. INCREMENTS. (MATING CABLE INCLUDED)  
 [W] IS 6 FT. CABLE WITH OPTIONAL BULKHEAD CONNECTOR PS/2 ONLY (LEGACY).

SPECIFICATION:

TEMPERATURE: -40°C TO +80°C  
 SEALING: NEMA 4 (IP66)  
 WEIGHT: KEYBOARD WITH STAINLESS STEEL ENCLOSURE  
 APPROX. 7lbs 4.55oz [ 3.30 KILOGRAMS]  
 STANDARDS: CE, ROHS, REACH, FCC CLASS B

NOTE: DIMENSIONS ARE IN INCHES MILLIMETERS

K I F 9 0 [ ] [ ] [ ] [ ] - N 2 - [ ] [ ]

ORDERING INFORMATION:

2B, 3B OR BLANK PS/2, 2B OR 3B MOUSE EMULATION (LEGACY)  
 FR FRENCH ``AZERTY'' (GRAY ELASTOMER)  
 ES SPANISH ``QWERTY'' (GRAY ELASTOMER)  
 DL GERMAN ``QWERTZ'' (GRAY ELASTOMER)  
 BLANK IS DEFAULT US ``QWERTY'' (GRAY/BLACK ELASTOMER)

G MAXIMUM COMPRESSION SPRING OPTION.  
 RF CONDUCTIVE BOOT OPTION.

1 GRAY ELASTOMER WITH SYN-PROOF COATING (TM) (WAS No.9)  
 4 BLACK ELASTOMER WITH SYN-PROOF COATING (TM) (WAS No.5)

<b>CTI ELECTRONICS CORPORATION</b> WWW.CTIELECTRONICS.COM	
<b>NEMA 4X KEYBOARD KIF9000-N2 SERIES</b> <b>W/INDUSTRIAL MOUSE (116 KEYS)</b>	
<b>761875</b>	
APPROVED	DATE 01-05-17 DRAWN BY PSB
SHEET 1 OF 1	
COPYRIGHT 2017 CTI ELECTRONICS CORP. SPECIFICATIONS SUBJECT TO CHANGE WITHOUT NOTICE	