

USB Flight Stick Testing Procedure

Below are instructions for testing the CTI Industrial Joystick as a USB Flight Stick in the following OS settings:

Start Plug in USB FlightStick into a USB port on the computer.
(Wait for USB FlightStick to be detected and enumerate itself – computer will acknowledge)

Windows 7:

First go to >> “Windows Logo” >> “Devices and Printers”:

Right Click “USB Input Device”, then select “Game Controller settings”

You will see “3 axis 8 button joystick” then Select “Properties”

(A visual Test window will appear – testing can now be performed)

Move joystick in both X & Y axis - you’ll see the cursor movement on the Test window.

If 3-Axis Joystick (N82 or N84 knob) move Z axis - you’ll see the cursor movement on the Test window.

Press the buttons on the switch pad (M2, H2, F8, M9) and the joystick (N3, N33, N34 knob options) - you’ll see the corresponding button illuminate in the Test window.

Windows XP:

First go to >> “My Computer” >> “Control Panel” >> “Printers and Other Hardware” >> “Game Controllers”:

Select “Properties”

(A visual Test window will appear – testing can now be performed)

Move joystick in both X & Y axis - you’ll see the cursor movement on the Test window.

Press the buttons on the switch pad (M2, H2, F8, M9) and the joystick (N3, N33, N34 knob options) - you’ll see the corresponding button illuminate in the Test window.

Windows 2000:

First go to >> “My Computer” >> “Control Panel” >> “Gaming Options”:

Select “Properties”

(A visual Test window will appear – testing can now be performed)

Move joystick in both X & Y axis - you’ll see the cursor movement on the Test window.

Press the buttons on the switch pad (M2, H2, F8, M9) and the joystick (N3, N33, N34 knob options) - you’ll see the corresponding button illuminate in the Test window.

Windows 98:

First go to >> “My Computer” >> “Control Panel” >> “Gaming Options”:

Select “Properties”

(A visual Test window will appear – testing can now be performed)

Move joystick in both X & Y axis - you’ll see the cursor movement on the Test window.

Press the buttons on the switch pad (M2, H2, F8, M9) and the joystick (N3, N33, N34 knob options) - you’ll see the corresponding button illuminate in the Test window.

CTI ELECTRONICS CORPORATION, STRATFORD, CT		
TITLE: INDUSTRIAL JOYSTICK / USB FLIGHTSTICK TESTING PROCEDURE		
REV. C	DATE:08/13/13	811802
APPROVED: PJM	DRAWN: PJK	