



when reliability is critical™

**Inductive Industrial Joysticks Reliability Data**  
**F1800-N82 Series – NEMA 12 (IP 54) 3 Axes Precision Control Joysticks**

Document No. 820103

Rev. 1/18/2011

**1) Electrical**

Power	10mA @ 5VDC (typical)
Repeatability	>1%
Accuracy	>1% of full scale (typical) >2% of full scale (worst case)

**2) Environmental**

Operating Temperature	0° to 80° C (standard) -40° to 80° C (with “D” option)
Storage Temperature	-40° to 80° C
Relative Humidity	100% non-condensing (with “Z” option)

**3) Sealing**

Drip Proof	Z Axis NEMA 12 (IP54), suitable for indoor use.
Water Resistant	X&Y Axes NEMA 4 (IP66) Sealing Boot

**4) Reliability**

MTBF	Greater than 100,000 hours
Life	10,000,000 random deflections

**5) Shock**

Peak Value	10 g
Pulse Duration	11 ms
Waveform	Half Sine

**6) Vibration**

Frequency	Displacement (inches)
5-25 Hz	0.1
25-55 Hz	0.03

**7) Certifications/Compliance**

Compliant with FCC class A and B regulations

“CE” classification option requires the following modifications:

- a.) Ferrite bead on ribbon cable (made by CTI Electronics)
- b.) Shielded enclosure and shielded cable (made by customer)

Restriction of Hazardous Substances Directive or RoHS Compliant (Pb free)