

INDUSTRIAL ORBITALMOUSE™

Document # 820110

Revision 10/24/05

ORBITALMOUSE™

- Molded silicone rubber keys
- Excellent tactile feel, 2mm travel
- Available with back-lighting
- ORBITAL MOUSE™
 - Button style pointer uses one round button for cursor movement
 - Performs 360° of movement.

Features:

- OEM Design
- Sealed gold plated switch contacts
- Port compatible with all computers - no software drivers needed
- Repairable design
- Plug and Play
- Direct factory support
- No Drift Design
- No moving electrical parts or magnets
- Made in USA

Temperature Ratings:

| | |
|------------------------|--------------|
| Operating Temperature: | 0 to 80°C |
| Operating (Optional) | -40 to 80°C |
| Storage Temperature: | -40 to 80° C |

Reliability:

| | |
|------------------------------------|-----------------------------------|
| MTBF (Mean Time Between Failures): | 100,000 hours per MIL-HDBK-217F. |
| Shock Rating: | 50g 11ms - 1/2 sine |
| Sealing: | NEMA 4, 4X, (IP66) |
| Vibration: | Mil-Std-810F, Category 4 |
| Buttons | Rated for up to 10 million cycles |

Certifications:

- Meets FCC Class A
- Meets CE Requirements
- ESD rated to 15KV