



when reliability is critical™

Reliability and Specification Data
KIF8000 & KIF9000 Series Industrial Keyboards
KIO8000 & KIO9000 Series Industrial Keyboards

Document # 820114
Revision 1-25-2010

Industrial Keyboards with Industrial Mouse™ & Orbital Mouse® Mouse Pointers

- Anodized aluminum powder coated black or beige enclosure or a stainless steel enclosure
- Molded rubber elastomer keys rated for 10 million cycles
- Excellent tactile feel, 2mm key travel
- Industrial Mouse™ (Joystick Mouse Cursors) available with 9 joystick knob options
- Orbital Mouse® (Button Style Mouse Cursors)
- Optional French (AZERTY), Spanish (QWERTY), or German (QWERTZ) legends

Features

Two, stainless steel threaded mounting holes (in bottom plate)
Rugged NEMA 4, 4X (IP66) for harsh environments
Keys: 2mm travel with excellent tactile feedback
Repairable design
Gray or Black Elastomer
Plug and Play, Port compatible - no drivers required
Legends are silicon ink, oven cured, so as to thermally fuse the ink to the rubber
Direct factory support
Joystick withstands 25lbs of a static load
No drift pointer design
Made in the USA

Reliability

MTBF (Mean Time between Failures): for the electronics is greater than 100,000 hours
Operating Temperature: 0° to 80° C
Operating (Optional): -40° to 80° C
Storage Temperature: -40° to 80° C
Shock rating: 30g to 50g 11msec. half sine, depending on knob option
Vibration: 10-55 Hz @ 0.013 DA
Elastomer Switches: Rated for up to up to 10 million cycles
Keys: Sealed "Hard" gold plated switch contacts. CTI uses a minimum of 30 to 50 micro inches of Gold over 100 micro inches of Nickel over Copper on our keyboard switch contacts.

NEMA and IP Sealing and Protection Standards

NEMA 4, NEMA 4X (IP66)
Syn-Proof™ coating resists most oils and harsh chemicals
Optional Parylene® coating available

Certifications

Meets FCC Class A
Meets CE Requirements
ESD rated to 15KV

110 Old South Avenue • Stratford, CT 06615
Tel: (203) 386-9779 • Fax: (203) 378-4986 • www.ctielectronics.com