



ORDERING INFORMATION:

- 1 4-40 THREADED INSERTS
  - 2 WITHOUT THREADED INSERTS, ROUND BODY (SPECIAL ORDER ONLY)
  - 3 3 MM THREADED INSERTS
- Z CONFORMAL COATING  
DZ LOW TEMP AND CONFORMAL COATING  
R CONDUCTIVE BOOT  
RF CONDUCTIVE BOOT AND FERRITE BEAD  
E WITHOUT DEADBAND
- F [ ] [ ] [ ] [ ] -N3
- 0 STANDARD 2 AXES
  - 5 FRICTION HELD 2 AXES
  - 6 SINGLE AXIS
  - 7 FRICTION HELD 1 AXIS
- 0 WITHOUT NEUTRAL SWITCH
  - 1 NEUTRAL SWITCH (AVAILABLE ON +5V MODELS ONLY)

- 0 +12V IN, 3 TO 9V OUT
  - 1 +5V IN, 1.25 TO 3.75V OUT
  - 2 +/-5V IN, +/-5V OUT
  - 3 +/-12V IN, +/-10V OUT
  - 4 +5V IN, 0.5 TO 4.5V OUT
  - 5 +5V IN, 0 TO 5V OUT
  - 6 +/-10V IN, +/-10V OUT
- REF DWG. A761718 FOR ELECTRICAL DETAILS

<b>CTI</b> ELECTRONICS CORPORATION	
110 Old South Ave, Stratford, CT 06615 - Tel 203 / 386-9779 - Fax 203 / 378-4986 - www.ctielectronics.com	
TITLE: <b>MODEL F1000-N3 SERIES</b>	
REV. E DATE: 11-21-07	<b>A 761685</b>
APPROVED:	
DRAWN: S.SZERSZEN	