



ORDERING INFORMATION:

- 0 STANDARD 2 AXES
 - 5 FRICTION HELD 2 AXES
 - 6 SINGLE AXIS
 - 7 FRICTION HELD 1 AXIS
- 0 +12V IN, 3 TO 9V OUT
 - 1 +5V IN, 1.25 TO 3.75V OUT
 - 2 +/-5V IN, +/-5V OUT
 - 3 +/-12V IN, +/-10V OUT
 - 4 +5V IN, 0.5 TO 4.5V OUT
 - 5 +5V IN, 0 TO 5V OUT
 - 6 +/-10V IN, +/-10V OUT
- REF DWG. A761718 FOR ELECTRICAL DETAILS
- 1 4-40 THREADED INSERTS
 - 2 WITHOUT THREADED INSERTS, ROUND BODY (SPECIAL ORDER ONLY)
 - 3 3 MM THREADED INSERTS
- Z CONFORMAL COATING
 - DZ LOW TEMP AND CONFORMAL COATING
 - R CONDUCTIVE BOOT
 - RF CONDUCTIVE BOOT AND FERRITE BEAD
 - E WITHOUT DEADBAND
- 0 WITHOUT NEUTRAL SWITCH
 - 1 NEUTRAL SWITCH (AVAILABLE ON +5V MODELS ONLY)

CTI ELECTRONICS CORPORATION	
110 Old South Ave, Stratford, CT 06615 - Tel 203 / 386-9779 - Fax 203 / 378-4986 - www.ctielectronics.com	
TITLE: MODEL F1000-N63 SERIES	
REV. B DATE: 11-21-07	A 761780
APPROVED:	
DRAWN: S.SZERSZEN	