

- 2.) Refer to CTI Drawing 820030 for details on Waterproof Through Panel Connector option.
- 3.) Consult Factory for other configuration options.
- 4.) Refer to CTI Applications Note 811666 for ARROWMOUSE™ operation.
- Backlighting is powered through the PS/2 port.
 The dimming of the backlight LEDs is done using onboard keys. See CTI Document 811675 for details. Power Requirements: 100 mA @ 5 VDC (typical).

ORDERING INFORMATION:

KIA60P0-Bx - PS/2 COMPATIBLE BACKLIT KEYBOARD AND ARROWMOUSE™

KIA60P0W -Bx -PS/2 COMPATIBLE BACKLIT KEYBOARD AND ARROWMOUSE™ w/ waterproof through panel connector.

*Backlight color can be either Red or Green. For RED Backlight, specify "-BR". For GREEN Backlight, specify "-BG" in place of "-Bx" shown above..

		O111(E1:701720
CTT ELE	CTRONICS CORPORATION	
110 Old South Ave , S	tratford , CT 06615 - Tel 203 / 386-9	779 - Fax 203 / 378-4986 - www.ctielectronics.com
NEMA 4 Sealed Keyboard Model Number KIA6000-Bx Series		
APPROVED:	DRAWN: Ray Kirmaier	A820057