



- ORDERING INFORMATION:**
- P PS/2 INTERFACE (6 PIN MINI DIN CONNECTOR, 9.5 FT. DEFAULT LENGTH)
 - U USB INTERFACE (9.5 FT. DEFAULT LENGTH)
 - 1 RS232 REF: DRAWING 811610 CABLE OPTION, 6.0 FT. DEFAULT LENGTH
 - 2 RS422/RS485 (CUSTOM PART No.)
 - USE ONLY IF POWER OPTION IS "0"
 - Q RS232 OPTIONAL CABLE REF. 811610 (CUSTOM CABLE LEGACY ONLY)
 - D LOW TEMPERATURE (-25°C TO +80°C)
 - Z CONFORMAL COATING ON PCB
 - V STANDARD VIBRATION DAMPENING
 - V1 LIGHT VIBRATION DAMPENING
 - 2B 2 BUTTON PS/2 MOUSE (LEGACY)
 - 3B OR BLANK 3 BUTTON PS/2 MOUSE (DEFAULT)
 - MSOF MICROSOFT SERIAL MOUSE (RS232 LEGACY)
- POWER OPTION**
- 0 STANDARD
 - 1 OPTIONAL RS232 POWER ADAPTOR CABLE
- Diagram:** A small schematic diagram showing a connector with pins labeled T 7, 3, and a dashed box containing two more pins.

SPECIFICATIONS SUBJECT TO CHANGE WITHOUT NOTICE

CTI ELECTRONICS CORPORATION WWW.CTIELECTRONICS.COM	
NEMA 12 (IP54) PANEL MOUNT INDUSTRIAL TRACKBALL 1.5" DIAMETER T7003 SERIES	
761258	SCALE 1-1
APPROVED	DATE 08-14-13
	DRAWN BY SJS/PSB