



SWITCH SEAL CLEAR

FOAM RUBBER FOOT

SILICONE GASKET

PAINTED ALUMINUM BOTTOM PLATE

PAINTED CRS ENCLOSURE

#8-32 MOUNTING HOLE PROVIDED FOR SECURING UNIT TO WORKING SURFACE (CENTERED IN THE "X" PLANE)

OPTIONAL HAND REST
GRAY SILICONE

- NOTES:**
1. SWITCHES: SEALED, 5 MILLION LIFE, GOLD CONTACTS.
 2. TRACKBALL MTBF: 100,000 HOURS
 3. POWER: 5 VOLTS @ 60 MILLIAMPS TYP.

ORDERING INFORMATION:

- USE ONLY IF POWER OPTION IS "0"
 - Q RS232 OPTIONAL CABLE REF. B811610 WITH "AT" CONNECTOR (LEGACY)
 - P RS232 OPTIONAL CABLE REF. B811610 WITH PS/2 CONNECTOR (LEGACY)
 - DZ LOW TEMPERATURE AND CONFORMAL COATED PCB
 - Z CONFORMAL COATED PCB
 - V VIBRATION DAMPENED
 - H OPTIONAL HAND REST
 - 2B 2 BUTTON PS/2 MOUSE (LEGACY)
 - 3B 3 BUTTON PS/2 MOUSE (DEFAULT)
 - MSOF MICROSOFT SERIAL MOUSE (RS232)
 - P PS/2 INTERFACE (6 PIN MINI DIN CONNECTOR, 9.5 FT. DEFAULT LENGTH)
 - U USB INTERFACE (9.5 FT. DEFAULT LENGTH)
 - 1 RS232 (REQUIRES A POWER ADAPTOR OR "Q" CABLE OR "P" CABLE OPTION, 6.0 FT. DEFAULT LENGTH)
- POWER OPTION
- 0 STANDARD
 - 1 OPTIONAL RS232 POWER ADAPTOR CABLE

CTI ELECTRONICS CORPORATION	
110 Old South Ave., Stratford, CT 06615 - Tel 203 / 386-9779 - Fax 203 / 378-4986 - www.ctielelectronics.com	
TITLE: MODEL T8XX3 SERIES 2.0" DIA. DESKTOP TRACKBALL	
REV. D DATE: 11-21-07	B 761470
APPROVED: _____ DRAWN: SJS	