



ORDERING INFORMATION:

- RF OPTIONAL CONDUCTIVE BOOT AND FERRITE BEAD
- Q RS232 OPTIONAL CABLE REF. B811610
- T OPTIONAL USB FLIGHT STICK PROGRAM (NON-MOUSE)
- W INDICATES OPTIONAL "W" TYPE BULKHEAD CONNECTOR

[] THRU 5 INDICATES "W" CABLE LENGTH DIMENSION IN 1 FOOT INCREMENTS
 BLANK [] INDICATES DEFAULT CABLE LENGTH OF 6 FEET

M9 [] [] 9 [] [] - [] [] - [] []

OPTIONS (BLANK INDICATES DEFAULT)

- 0 STANDARD
- 1 OPTIONAL RS232 POWER ADAPTOR CABLE

- P PS/2 INTERFACE (6 PIN MINI DIN CONNECTOR, 9.5 FT. DEFAULT LENGTH)
- U USB INTERFACE (9.5 FT. DEFAULT LENGTH)
- 1 RS232 (REQUIRES EITHER A POWER ADAPTOR OR A "Q" CABLE OPTION, 6.0 FT. DEFAULT LENGTH)

BLANK OR

- 2B 2 BUTTON EMULATION PS/2 MOUSE (LEGACY)
- 3B 3 BUTTON EMULATION PS/2 MOUSE (DEFAULT)
- MSOF MICROSOFT SERIAL MOUSE (RS232)

KNOB OPTION

CTI ELECTRONICS CORPORATION	
110 Old South Ave., Stratford, CT 06615 - Tel 203 / 386-9779 - Fax 203 / 378-4986 - www.ctielelectronics.com	
TITLE: NEMA (IP66) 4X DESKTOP INDUSTRIAL MOUSE® MODEL M9XX9-NX SERIES	
REV. dDATE: 11-05-08	B 761689
APPROVED: VI / SJS	