



MOUNTING SCREWS
INSTALLED IN FIELD
(x8)

MOUNTING HARDWARE INCLUDED

1	RAIL INSTALLATION INSTRUCTION SHEET No. 811594 FOR 2U MODEL KIT30X3
1	PACKAGE OF EXTRA (2) SHORT BRACKETS #10-32 SCREWS & NUTS GENERAL DEVICES
2	PACKAGES OF MODIFIED 701641-1 GENERAL DEVICES #C-774-18-RC
1	SET EXTENSIONS BRACKETS (2 PC) GENERAL DEVICES #CB8062-06-0010
4	#10-32 NUTS (FOR SECURING EXTENSIONS BRACKETS) GENERAL DEVICES
8	PAN HEAD SCREWS #8-32 x 3/8 LG. (#8C37MPPS STAINLESS STEEL)
8	#8 FLAT WASHERS (#AN960C8 STAINLESS STEEL)
8	#8-32 HEX NUTS (#8CNHMS STAINLESS STEEL)

NOTES

- 1 RAILS MOUNTING DISTANCE 18" FRONT TO BACK
- 2 EXTENSIONS BRACKETS PROVIDED FOR 18" TO 24" DEPTH. RATED LOAD FOR 80 LBS/ EACH
- 3 RAILS LOCK IN EXTENDED POSITION. 13.5" TRAVEL
- 4 FRAME & MOUNTING PLATE 1/8" THICK ALUMINUM, PAINTED BEIGE COLOR
- 5 (MOUNTING HARDWARE INCLUDED), SEE TABLE

KIF30U3-3B USB INTERFACE CABLE LENGTH = 9.5 FT
 KIF30P9-3B PS/2 INTERFACE CABLE LENGTH = 9.5 FT
 KIF3019-MSOF (LEGACY) SERIAL MOUSE ``D9" CONNECTOR, "AT" KEYBOARD (5 PIN CIRCULAR DIN) CONNECTOR. CABLE LENGTH = 6 FT.

CTI ELECTRONICS CORPORATION 110 OLD SOUTH AVE, STRATFORD, CT 06615 WWW.CTIELECTRONICS.COM	MODEL KIF30X9 SERIES 2U RACKMOUNT KEYBOARD	
	B 761704	REV. C
DRAWN PSB	DATE 03-12-10	SHEET 1 OF 1