



when reliability is critical™

Reliability and Specification Data KXT2700 Series Keyboards

Document # 820106
Revision 1-25-2010

Industrial Keyboards with built-in Industrial Trackball Mouse Pointers

- Anodized aluminum enclosure in beige or black
- Molded rubber elastomer keys
- Excellent tactile feel, 2mm key travel
- 1.5" diameter Trackballs (Trackball Mouse Cursors)
- Optional French (AZERTY), Spanish (QWERTY), or German (QWERTZ) legends
- SUN, Serial, PS/2, or USB Interface with optional Bulkhead Cable Set (Waterproof)

Features

Two stainless steel threaded mounting holes (in bottom plate)
Trackball has Teflon seal in aluminum collar.
Repairable design
Plug and Play
Direct factory support
Calculated rolling life of trackball bearings is 20 years
No rubber or foam on trackball rollers, no cleaning is required
Made in the USA

Reliability

MTBF (Mean Time between Failures):	Electronics is greater than 100,000 hours
Operating Temperature:	0° to 80° C
Operating (Optional)	-40° to 80° C
Storage Temperature:	-40° to 80° C
Shock rating:	30g 11msec. half sine, three axes
Vibration:	10-55 Hz@ 0.013 DA
Elastomer Switches:	Rated for 10 million cycles
Keys:	Sealed "Hard" gold plated switch contacts.

NEMA and IP Sealing and Protection Standards

NEMA 12 (IP54) Trackball, NEMA 4 Keyboard
Syn-Proof™ coating resists most oils and harsh chemicals
Optional Parylene® coating available

Certifications

Meets FCC Class A
Meets CE Requirements
ESD rated to 15KV