


ORDERING INFORMATION:

- 0 GRAY ELASTOMER
 - 1 GRAY ELASTOMER WITH SYN-PROOF COATING™
 - 4 BLACK ELASTOMER WITH SYN-PROOF COATING™
 - 5 BLACK ELASTOMER
- [W] INDICATES OPTIONAL "W" TYPE BULKHEAD CONNECTOR
- [1] THRU 5 INDICATES "W" CABLE LENGTH DIMENSION IN 1 FOOT INCREMENTS
- BLANK INDICATES DEFAULT CABLE LENGTH OF 6 FEET
- I STANDARD QWERTY (IBM)
 - C SUN LEGEND
 - 5C SUN VERSION (LEGACY)
 - ES SPANISH
 - FR FRENCH
 - DL GERMAN
- 0 STAINLESS STEEL ENCLOSURE
 - 5 ALUMINUM ENCLOSURE, PAINTED BEIGE
 - P PS/2 INTERFACE (6 PIN MINI DIN CONNECTOR, 9.5 FT. DEFAULT LENGTH)
 - T "AT" INTERFACE (5 PIN CIRCULAR DIN CONNECTOR, 6.0 FT. DEFAULT LENGTH)
 - U USB INTERFACE (9.5 FT. DEFAULT LENGTH)
 - S SUN INTERFACE (8 PIN MINI DIN CONNECTOR, 6.0 FT. DEFAULT LENGTH) (LEGACY)
 - 1 RS-232 SERIAL ASC11 (REF. P-FILE FOR CABLE DETAILS)



CTI ELECTRONICS CORPORATION <small>110 Old South Ave., Stratford, CT 06615 · Tel 203 / 386-9779 · Fax 203 / 378-4986 · www.ctielelectronics.com</small>	
TITLE: NEMA 4/4X KEYBOARD MODEL KX9XXX SERIES	
REV. DATE: 09-22-04	<h1>B 761681</h1>
APPROVED: DRAWN: SJS / VI	