



0 STANDARD DEFAULT
1 OPTIONAL RS232 POWER ADAPTOR CABLE, (REQUIRED FOR ``MSOF'' OPTION LEGACY REF. 8II610)

P PS/2 INTERFACE (6 PIN MINI DIN CONNECTOR, 9.5 FT. DEFAULT CABLE LENGTH)

U USB INTERFACE (9.5 FT. DEFAULT CABLE LENGTH)

I RS232 (REQUIRES POWER ADAPTOR OPTION, 6.0 FT. DEFAULT CABLE LENGTH, OR 'P' FILE)

2 RS422/RS485 CONSULT FACTORY FOR ``P'' FILE NO.

T USB HID COMPLIANT GAME CONTROL DEVICE

DZ LOW TEMP AND CONFORMAL COATING

RF OPTIONAL CONDUCTIVE BOOT AND FERRITE BEAD

G MAXIMUM COMPRESSION SPRING OPTION. (N3,N33,ONLY)

[W1] THRU [W5] INDICATES OPTIONAL BULKHEAD CONNECTOR,
1 THRU 5 FOOT CABLE LENGTH IN 1 FT. INCREMENTS.
(MATING CABLE INCLUDED)

3	N3 BLACK ABS KNOB
33	N33 BLACK DELRIN KNOB
63	N63 BLACK DELRIN KNOB

2B, 3B OR BLANK	PS/2, 2B OR 3B MOUSE EMULATION (LEGACY)
MSOF	MICROSOFT SERIAL MOUSE (RS232 LEGACY)

ORDERING INFORMATION:

SPECIFICATIONS

TEMPERATURE: -40°C TO +80°C

SEALING: NEMA 4 (IP66)

WEIGHT: M90U9-N3 = 2.LB 2.OZ [.964 KILOGRAMS] TYPICAL

STANDARD: CE, RoHS, REACH, FCC CLASS B

CTI ELECTRONICS CORPORATION

WWW.CTIELECTRONICS.COM

NEMA 4X (IP66)
DESKTOP INDUSTRIAL MOUSE™
OR USB FLIGHTSTICK
M9XX9-NX SERIES

761689

DRAWN BY PSB

DATE 05-10-17

APPROVED

SHEET 1 OF 1

NOTE: DIMENSIONS ARE IN INCHES [MILLIMETERS]

COPYRIGHT 2017 CTI ELECTRONICS CORP.
SPECIFICATIONS SUBJECT TO CHANGE WITHOUT NOTICE