



- 4 ALUMINUM ENCLOSURE, PAINTED BLACK
- 5 ALUMINUM ENCLOSURE, PAINTED BEIGE (LEGACY)
- P PS/2 INTERFACE (6 PIN MINI DIN CONNECTOR, 9.5 FT. DEFAULT CABLE LENGTH)
- U USB INTERFACE (9.5 FT. DEFAULT CABLE LENGTH)

[W1] THRU [W5] INDICATES OPTIONAL BULKHEAD CONNECTOR, 1 THRU 5 FOOT CABLE LENGTH IN 1 FT. INCREMENTS. (MATING CABLE INCLUDED)

[W] IS 6 FT. CABLE WITH OPTIONAL BULKHEAD CONNECTOR PS/2 ONLY (LEGACY).

ORDERING INFORMATION:

K I F 8 [] [] [] [] - N 2 - []

2B, 3B OR BLANK	PS/2, 2B OR 3B MOUSE EMULATION (LEGACY)
FR FRENCH ``AZERTY''	(GRAY ELASTOMER)
ES SPANISH ``QWERTY''	(GRAY ELASTOMER)
DL GERMAN ``QWERTZ''	(GRAY ELASTOMER)
BLANK IS DEFAULT	US ``QWERTY'' (GRAY/BLACK ELASTOMER)

G MAXIMUM COMPRESSION SPRING OPTION.

RF CONDUCTIVE BOOT OPTION.

1 GRAY ELASTOMER WITH SYN-PROOF COATING (TM) (WAS 9)

BLACK ELASTOMER WITH SYN-PROOF COATING (TM) (WAS 5)

- SPECIFICATIONS:**
- TEMPERATURE: -40°C TO +80°C
 - SEALING: NEMA 4 (IP66)
 - WEIGHT: KEYBOARD WITH ALUMINUM ENCLOSURE APPROX. 3lbs 4.05oz [1.48 KILOGRAMS]
 - STANDARDS: CE, ROHS, REACH, FCC CLASS B

CTI ELECTRONICS CORPORATION
 WWW.CTIELECTRONICS.COM

MODEL KIF8000-N2 SERIES

761699

APPROVED SHEET 1 OF 1 DATE 12-22-16 DRAWN BY PSB

COPYRIGHT 2016 CTI ELECTRONICS CORP.
 SPECIFICATIONS SUBJECT TO CHANGE WITHOUT NOTICE

NOTE: DIMENSIONS ARE IN INCHES MILLIMETERS