



SPECIFICATIONS:

TEMPERATURE: -40°C TO +80°C

SEALING: NEMA 4 (IP66)

WEIGHT: KEYBOARD WITH ALUMINUM ENCLOSURE APPROX. 3lbs 4.5oz [1.49 KILOGRAMS]
WITH N33 KNOB (OPTIONAL) APPROX. 3lbs 5.oz [1.50 KILOGRAMS]

STANDARDS: CE, ROHS, REACH, FCC CLASS B

4 ALUMINUM ENCLOSURE, PAINTED BLACK
5 ALUMINUM ENCLOSURE, PAINTED BEIGE (LEGACY)

P PS/2 INTERFACE (6 PIN MINI DIN CONNECTOR, 9.5 FT. DEFAULT CABLE LENGTH)
U USB INTERFACE (9.5 FT. DEFAULT CABLE LENGTH)

[W1] THRU [W5] INDICATES OPTIONAL BULKHEAD CONNECTOR, 1 THRU 5 FOOT CABLE LENGTH IN 1 FT. INCREMENTS. (MATING CABLE INCLUDED)

[W] IS 6 FT. CABLE WITH OPTIONAL BULKHEAD CONNECTOR PS/2 ONLY (LEGACY).

ORDERING INFORMATION:

K I F 8

2B, 3B OR BLANK PS/2, 2B OR 3B MOUSE EMULATION (LEGACY)
FR FRENCH "AZERTY" (GRAY ELASTOMER)
ES SPANISH "QWERTY" (GRAY ELASTOMER)
DL GERMAN "QWERTZ" (GRAY ELASTOMER)
BLANK IS DEFAULT US "QWERTY" (GRAY/BLACK ELASTOMER)

3 OR 33 ONLY

G MAXIMUM COMPRESSION SPRING OPTION.
RF CONDUCTIVE BOOT OPTION.

1 GRAY ELASTOMER WITH SYN-PROOF COATING™ (WAS 9)
4 BLACK ELASTOMER WITH SYN-PROOF COATING™ (WAS 5)

NOTE: DIMENSIONS ARE IN INCHES [MILLIMETERS]

CTI ELECTRONICS CORPORATION
WWW.CTIELECTRONICS.COM

MODEL KIF8000-N3 SERIES

761717

APPROVED SHEET 1 OF 1 DATE 12-22-16 DRAWN BY PSB

COPYRIGHT 2016 CTI ELECTRONICS CORP.
SPECIFICATIONS SUBJECT TO CHANGE WITHOUT NOTICE