



ORDERING INFORMATION:

- P PS/2 INTERFACE
 - U USB INTERFACE
 - 0 ALUMINUM ENCLOSURE, PAINTED BEIGE
 - 4 ALUMINUM ENCLOSURE, PAINTED BLACK
 - 6 STAINLESS STEEL ENCLOSURE
 - 1 GRAY ELASTOMER WITH SYN-PROOF COATING (WAS 0)
 - 4 BLACK ELASTOMER WITH SYN-PROOF COATING
 - BLANK US (QWERTY) BLACK/GREY ELASTOMER
 - DL GERMAN BLACK ELASTOMER
 - ES SPANISH BLACK ELASTOMER
 - FR FRENCH (AZERTY) GREY ELASTOMER
- K I 6
- [W1] THRU [W5] INDICATES OPTIONAL BULKHEAD CONNECTOR, 1 THRU 5 FOOT CABLE LENGTH IN 1 FT. INCREMENTS. (MATING CABLE INCLUDED)
- [W] IS 6 FT. CABLE WITH OPTIONAL BULKHEAD CONNECTOR PS/2 ONLY (LEGACY).

SPECIFICATION:

- TEMPERATURE: -40°C TO +80°C
- SEALING: NEMA 12 (IP54)
- SHOCK: 40G (N) 11 msec. per MIL-STD-810
- WEIGHT: KEYBOARD IN ALUMINUM ENCLOSURE APPROX. 21.7 OZ. (.61 KILOGRAMS)
- KEYBOARD IN STAINLESS STEEL ENCLOSURE APPROX. 40.OZ. (1.13 KILOGRAMS)
- STANDARDS: CE, ROHS, REACH, FCC CLASS B

NOTE: DIMENSIONS ARE IN INCHES [MILLIMETERS]

CTI ELECTRONICS CORPORATION	
WWW.CTIELECTRONICS.COM	
NEMA 4X/IP66	
INDUSTRIAL KEYBOARD	
KI6000 SERIES	
761724	SHEET 1 OF 1
APPROVED	DATE 09-29-16
DRAWN BY PSB	
COPYRIGHT 2016 CTI ELECTRONICS CORP.	
SPECIFICATIONS SUBJECT TO CHANGE WITHOUT NOTICE	