



ORDERING INFORMATION:

K|O 6 □ U 4- □ - □ □

LANGUAGE OPTIONS

BLANK IS QWERTY
 DL GERMAN
 ES SPANISH
 FR FRENCH

BG BACKLIT GREEN
 BR BACKLIT RED

4 BLACK ELASTOMER

U USB INTERFACE (9.5 FT. CABLE LENGTH)

0 ALUMINUM ENCLOSURE, PAINTED BEIGE
 4 ALUMINUM ENCLOSURE, PAINTED BLACK
 6 STAINLESS STEEL ENCLOSURE

SPECIFICATION:

TEMPERATURE: -40°C TO +80°C
 SEALING: NEMA 4/4X (IP66)
 SHOCK: 40G (N) 11 msec. per MIL-STD-810
 WEIGHT: ALUMINUM: 1 Lb 6.5 OZ (638 GRAMS)
 STAINLESS STEEL: 2 Lb 8 OZ (1134 GRAMS)
 STANDARD: ☑ ROHS, REACH, FCC CLASS B
 PATENTS: 7,499,032, OTHERS PENDING

CTI ELECTRONICS CORPORATION

WWW.CTIELECTRONICS.COM

NEMA 4/4X (IP66) INDUSTRIAL KEYBOARD
 WITH ORBITAL MOUSE®
 (BUTTON STYLE POINTER)
 KIO6000-BX BACKLIT SERIES

761801

SHEET 1 OF 1

DATE 10-14-15

APPROVED

DRAWN BY PSB

COPYRIGHT 2015 CTI ELECTRONICS CORP.
 SPECIFICATIONS SUBJECT TO CHANGE WITHOUT NOTICE