



0 STANDARD DEFAULT  
 1 OPTIONAL RS232 POWER ADAPTER CABLE  
 U USB INTERFACE (9.5 FT. DEFAULT CABLE LENGTH)  
 1 RS232      2 RS422/RS485      OPTIONAL CUSTOMER INTERFACE REQUIRES "P" FILE  
 T USB HID COMPLIANT GAME CONTROL DEVICE  
 DZ LOW TEMP AND CONFORMAL COATING  
 RF OPTIONAL CONDUCTIVE BOOT AND FERRITE BEAD  
 G MAXIMUM COMPRESSION SPRING OPTION. (N8A,N82,ONLY)  
 [W1] THRU [W5] INDICATES OPTIONAL BULKHEAD CONNECTOR,  
 1 THRU 5 FOOT CABLE LENGTH IN 1 FT. INCREMENTS.  
 (MATING CABLE INCLUDED)  
 M 9 [ ] 9 [ ] - N 8 [ ] A N8A ALUMINUM KNOB, WITH FINE KNURL BLACK ANODIZE  
 2 N82 BLACK DELRIN KNOB  
 4 N84 BLACK DELRIN KNOB

#### ORDERING INFORMATION:

#### SPECIFICATIONS

TEMPERATURE: -40°C TO +80°C  
 SEALING: N84 NEMA 4X (IP66)  
 N82/N8A NEMA I2 (IP54)  
 WEIGHT: M90U9-N82= 2.LB 2.OZ [.963 KILOGRAMS] TYPICAL  
 STANDARD: CE, RoHS, REACH, FCC CLASS B

**CTI ELECTRONICS**  
[WWW.CTELECTRONICS.COM](http://WWW.CTELECTRONICS.COM)  
 NEMA 4X NEMA I2 (IP66/IP54)  
 DESKTOP INDUSTRIAL 3 AXES CONTROLLER  
 OR USB FLIGHTSTICK  
 M90X9-N8X SERIES

761884

DRAWN BY PSB  
 DATE 10-4-17

APPROVED

SHEET 1 OF 1

COPYRIGHT 2017 CTI ELECTRONICS  
 SPECIFICATIONS SUBJECT TO CHANGE WITHOUT NOTICE