



- 0 STANDARD DEFAULT
- 1 OPTIONAL RS232 POWER ADAPTER CABLE
- P PS/2 INTERFACE (6 PIN MINI DIN CONNECTOR, 9.5 FT. DEFAULT CABLE LENGTH)
- U USB INTERFACE (9.5 FT. DEFAULT CABLE LENGTH)
- 1 RS232
- 2 RS422/RS485
- T USB HID COMPLIANT GAME CONTROL DEVICE
- DZ LOW TEMP AND CONFORMAL COATING
- RF OPTIONAL CONDUCTIVE BOOT AND FERRITE BEAD
- G MAXIMUM COMPRESSION SPRING OPTION. (N8A,N82,ONLY)
- [W1] THRU [W5] INDICATES OPTIONAL BULKHEAD CONNECTOR, 1 THRU 5 FOOT CABLE LENGTH IN 1 FT. INCREMENTS. (MATING CABLE INCLUDED)
- 2 N2 GRAY PVC
- 24 N24 GRAY PVC
- 2B, 3B OR BLANK PS/2, 2B OR 3B MOUSE EMULATION (LEGACY)

ORDERING INFORMATION:

SPECIFICATIONS

TEMPERATURE: -40°C TO +80°C
 SEALING: N2/N24 NEMA 4X (IP66)
 WEIGHT: M90U9-N2= 2Lbs 1.0 oz [.935 KILOGRAMS] TYPICAL
 STANDARD: CE, RoHS, REACH, FCC CLASS B

NOTE: DIMENSIONS ARE IN INCHES[MILLIMETERS]

CTI ELECTRONICS WWW.CTIELECTRONICS.COM	
NEMA 4X (IP66) DESKTOP INDUSTRIAL MOUSE™ OR USB FLIGHTSTICK M9XX9-N2X SERIES	
761885	DRAWN BY PSB DATE 10-5-17
APPROVED	SHEET 1 OF 1
COPYRIGHT 2017 CTI ELECTRONICS SPECIFICATIONS SUBJECT TO CHANGE WITHOUT NOTICE	