





Notes:

- 1.) All Dimensions are in inches.
- 2.) The industry exclusive N3 handle includes a NEMA 4 sealed pushbutton that duplicates the "Left Mouse Button" function. Refer to CTI Electronics Applications Note 811613 and 811629 for Industrial Mouse® operation.
- 3.) Any of the handle options shown above may be used for the Industrial Mouse. Please specify at time of order. i.e., Model Number F90P9-N24-3B uses the N24 handle.
- 4.) This product contains static sensitive components. Use appropriate static precautions when handling and installing this product into OEM final assembly.
- 5.) Unit mounts from below panel using (4) 4-40 stainless steel or nylon screws or studs. Screws to extend a maximum of 1/8" below bottom of panel.
- 6.) Consult Factory for other configuration options.

ORDERING INFORMATION:

F90P9-N3-3B - OEM Industrial Mouse® for Panel Mounting, PS/2 mouse port compatible.

F9019 Series - OEM Industrial Mouse® for Panel Mounting for Serial Port applications.

(Refer to CTI Applications Drawing 811665 for details).

Operating Temperature Range -25°C to 70°C Standard -40°C to 80°C Optional

Watertight to NEMA 4

Net Weight 10 oz.

Industrial Mouse® is a Registered Trademark of Not to Scale CTI Electronics Corporation

CTI REF: 761687 ve . Stratford . CT 06615 - Tel 203 / 386-9779 - Fax 203 / 378-4986 - www.ctielectronics.com F9 Series Industrial Mouse **NEMA 4 Rated** 08/29/00 A820045 : Ray Kirmaiei