

- P PS/2 INTERFACE (6 PIN MINI DIN CONNECTOR, 9.5 FT. DEFAULT LENGTH)
- U USB INTERFACE (9.5 FT. DEFAULT LENGTH)
- 1 RS232 REF: DRAWING 811610 CABLE OPTION, 6.0 FT. DEFAULT LENGTH
- 2 RS422/RS485 (CUSTOM PART No.)

USE ONLY IF POWER OPTION IS "0"  
 Q RS232 OPTIONAL CABLE REF. 811610 (CUSTOM CABLE LEGACY ONLY)


- DZ LOW TEMPERATURE (-25°C TO 80°C) & CONFORMAL COATING (ENCODER PCB'S)
- Z CONFORMAL COATING ON PCB
- V STANDARD VIBRATION DAMPENING
- V1 LIGHT VIBRATION DAMPENING

- 2B 2 BUTTON PS/2 MOUSE (LEGACY)
- 3B OR BLANK 3 BUTTON PS/2 MOUSE (DEFAULT)
- MSOF MICROSOFT SERIAL MOUSE (RS232 LEGACY)

ORDERING INFORMATION:

POWER OPTION

- 0 STANDARD
- 1 OPTIONAL RS232 POWER ADAPTOR CABLE



SPECIFICATIONS SUBJECT TO CHANGE WITHOUT NOTICE

|  |                     |
|--|---------------------|
| <b>CTI</b> ELECTRONICS CORPORATION<br>WWW.CTIELECTRONICS.COM                     |                     |
| NEMA 12 (IP54) PANEL MOUNT<br>INDUSTRIAL TRACKBALL 2.0" DIAMETER<br>T1000 SERIES |                     |
| <b>761128</b>  | REV. H              |
| APPROVED   | DATE 10-10-13       |
|  | DRAWN BY<br>SJS/PSB |