



when reliability is critical™

How to Select a Medical / Cleanroom Keyboard

Congratulations! You have found the world's best medical keyboards. Why? Because CTI Electronics Corporation completely designs and manufactures all of the critical sensors, components, circuitry, and firmware necessary to ensure our customers guaranteed **long term availability**. CTI's medical keyboards have survived 25 years of service; this high **durability** of success is due to the uses a thick layers of hard gold, protective shielding from shocks, vibration, and effects of high EMI and RFI signals. The **reliability** is unquestionable; 7x24x365 in the harshest of environments these medical keyboards take a beating and keep on performing without fault. That's why we say, "When Reliability is Critical" you need to talk with us. CTI's offers Commercial Off The Shelf (COTS) Medical Keyboards as well as customized (Build to Print) manufacturing. Advanced rapid prototyping and optimization to your demanding requirements is available.

Simply, CTI's NEMA 4 (IP66) sealing medical keyboard is comprised of a Printed Circuit Board and a rubber elastomer with a Syn-Proof Coating (Resists harsh oils, chemicals, and debris). Yet, it's so complex that its prevents pressurized water seepage and operates in a temperature range between -40°C and +80°C. CTI is so confident is these medical keyboards that it offers, an unheard of, five (5) year Repair Policy on it's Plug-n-Play medical keyboard.

To allow CTI to optimize the medical keyboard solution to the specific requirements of your application we ask that you provide as much detailed information as possible.

Describe the application of the Medical Keyboard (usage, how, where, when):

Select a stage of manufacture:

OEM – A medical keyboard that is mounted underneath a panel or into an enclosure.

Approximate Sizes:

Compact/Miniature (8"Wx5"H)	Mid-Size (12"Wx7"H)	Full-Size (15.5"Wx7"H)	Other
--------------------------------	------------------------	---------------------------	-------

Plug-n-Play – An medical keyboard that is enclosed aluminum or stainless steel that can be placed on a desk or mounted using the stainless steel inserts onto any surface.

Approximate Sizes:

Compact/Miniature (8.75"Wx6"Hx1.25"D)	Mid-Size (12.5"Wx6"Hx1.5"D)	Full-Size (20"Wx8"Hx1.5"D)	Other
Aluminum (NEMA 4 (IP66) sealing)		Stainless Steel (NEMA 4X (IP66) Sealing)	

Environment of Usage: Indoor Outdoor Both Other:

Operating Temperature Range: (-40°C to +80°C) (0°C to +80°C) Other:

Subjected to Hazardous Substances: Yes No
(check all that apply)

Liquids:	Water	Oil	Grease	Bio-Hazard	Chemical	Others:
Solids:	Dirt	Dust	Food	Bio-Hazard	Chemical	Others:
High Emission Signals:	EMI	RFI	Specifics:			

Will the Operator of the Medical Keyboard require a Mouse Pointing Device? Yes No

Describe the tasks an Operator will perform while using the Medical Mouse Pointing Device:

How many hours of an eight hour day will the Medical Mouse be used?
hours/day

If **yes**, select a pointing device based upon operator's frequency of usage, cursor speed, fluidity of movement, and size of the targets:

- **Medical Mouse** - Trademark first used in 1989, application of a Joystick mouse pointing device. (High Usage, Rapid Speed, Smooth Movement of 360° in very fine detail, target size >1mm(0.04"))
- **Orbital Mouse®** - Trademark first used in 2003, application of a Button Style, circular, mouse pointing device. (Low Usage, Variable Speed, Jumping Movement of 360° to approximate location, target size >25mm(1.0"))
- **Trackball** – The Ball mouse pointing device provides an IP65 sealing (static) and IP54 sealing (rotating). (Low to High Usage, Slow Speed, Precise Movement in exacting detail, target size ≤ 1mm(0.04")) e.g. tracing/outlining objects

Select the computer Operating System:

Windows Solaris Unix Linux Real-Time Other

Select the Communication Interface:

USB Other:

For OEM Medical Keyboards select a cable length: No

Plug-n-Play Medical Keyboards

Optional NEMA 4 (IP66) sealing Bulkhead Panel Cable Set: Yes No

CTI can manufacture the Plug-n-Play Medical Keyboards with a cable having a twist on Plug that connects to a Panel. A cut-out is made in the Panel and the second half of the cable (behind panel) set is securely fastened into the panel cut-out. The behind panel cable will then be connected the the computer system via a standard USB or PS/2 plug(s).

Bulkhead Cable Length (Feet): USB PS/2

Will the Operator of the Keyboard and/or Medical Mouse be using gloves? Yes No
Heavy/Thick Flexible/Thin Other

Is an Industrial Backlit Keyboard (illuminated) required? Yes No
Red LED's Green LED's Other

Is a full numeric keypad required? Yes No

Contact Information:

First: _____ Last: _____
 Company: _____
 Address 1: _____
 Address 2: _____
 City: _____ State/Province: _____ Country: _____ ZIP: _____
 Phone: _____ Fax: _____ E-mail: _____