



when reliability is critical™

## **Reliability and Specification Data KIO7000 Series Industrial Keyboards**

Document # 820115  
Revision 1-25-2010

### **Industrial Keyboards with Orbital Mouse® Mouse Pointers**

- Anodized aluminum enclosure powder coated beige or black
- Stainless steel enclosure available
- Molded rubber elastomer keys rated for 10 million cycles
- Excellent tactile feel, 2mm key travel
- Orbital Mouse™ (Button Style Mouse Cursors)
- Optional French (AZERTY), Spanish (QWERTY), German (QWERTZ), Italian (QWERTY) legend
- PS/2, or USB Interface with optional Bulkhead Cable

### **Features**

Two stainless steel threaded mounting holes (in bottom plate)  
Back lighting option: RED or GREEN LED's  
Black Elastomer with backlighting option  
Gray Elastomer standard  
Rugged NEMA 4, NEMA 4X (IP66) for harsh environments  
Keys: 2mm travel with excellent tactile feedback  
Repairable design  
Plug and Play, Port compatible - no drivers required  
Legends are silicon ink, oven cured, so as to thermally fuse the ink to the rubber  
Direct factory support  
Made in the USA

### **Reliability**

MTBF (Mean Time between Failures): Electronics is greater than 100,000 hours  
Operating Temperature: -40° to 80° C  
Storage Temperature: -40° to 80° C  
Shock rating: 50g 11msec. half sine, three axes  
Vibration: 10-55 Hz@ 0.013 DA  
Elastomer keys: Rated for up to 10 million cycles  
Keys: Sealed "Hard" gold plated switch contacts.

### **NEMA and IP Sealing and Protection Standards**

NEMA 4, NEMA 4X (IP66)  
Syn-Proof™ coating resists most oils and harsh chemicals  
Optional Parylene® coating available

### **Certifications**

Meets FCC Class A  
Meets CE Requirements, RoHS Compliant  
ESD rated to 15KV

### **United States Patents**

U.S. Patent No. 7,499,032  
U.S. Patents Pending 12/344368